



Impressive in size and flexibility

Maxiflex - Heavy duty tent configuration with almost limitless possibilities.


The maxiflex tent system, available from 10 - 50 meter widths, is the most versatile of our large tent systems. It is ideal for companies that frequently assemble tents larger than 30 m, but also hire out tents smaller than 30 m. Only one frame section is needed to create widths from 10 m to 50 m width with the maxiflex system. This system offers an attractive choice of configurations and designs in diverse sizes.

Everything in the system can be combined and interchanged. This ensures efficient storage, avoids handling problems and is highly economical. It goes without saying that the maxiflex tent system includes all options for future tent designs.

Maximize your creativity: System elements of glass or hard-PVC (with side heights of 3.40 and 4.00 m), system cassette flooring, aluminium doors, ramps, decoration and much more.



Dimensions

Type	Profile	Frame ID#	Truss Profile	Width	Leg	Truss-distance	Rafter Sections	
							Standard	Optional
maxiflex 	P1	5	300 mm x 120 mm	15 m	340/400/540 cm	5 m	7.5 m	5.0 m + 2.5 m
				20 m	340/400/540 cm		10.0 m	7.5 m + 2.5 m
				25 m	340/400/540 cm		7.5 m + 5.0 m	10.0 m + 2.5 m
				30 m	340/400/540 cm		10.0 m + 5.0 m	7.5 m + 7.5 m
				35 m	340/400/540 cm		10.0 m + 7.5 m	–
				40 m	340/400/540 cm		10.0 m + 10.0 m	–
				50 m	340/400 cm		10.0 m + 10.0 m + 5.0 m	–

Technology

Modular character for diverse combination and expansion. Trouble-free transport, storage and maintenance. Assembly with and without system cassette flooring possible. A host of accessories and special equipment. All system components are standard stock parts for fast availability. The interchangeable tent components within the system enable various configurations, different widths and extensions without expensive special solutions.

Frame

Trusses of extruded 4-groove aluminum hollow profiles, maintenance free, all aluminum components technically anodized. Steel parts are hot-dip galvanized. Truss distance 5m (16.5'). Roof slope 18 degrees. Integrated curtain groove in eave purlins and gable wall beams. Prepared for a subsequent installation of system cassette wall elements of hard-PVC or glass. Structural lengths in 5m increments. Exact joining of various large and small tent systems possible.

Covers

Textile covers made of polyester fabric, coated with PVC on both sides. Curtains with PVC-glidors for easy fitting in curtain groove. Side and gable curtains with standard plug fastening, lace and grommet or zippers. Side curtains with windows available in several attractive designs. System wall elements are available in glass or hard-PVC.

Accessories & special equipment options:

- Roof covers and side curtains of transparent foil
- Aluminum doors (double-wing/one-wing)
- Glass & Cassette wall
- Cassette floors
- Ramps at entrances
- Textile beam gutter or beam flap
- and many more...

For more details please visit our website
www.voloevents.com

